

	Type	L #	Hits	Search T xt	DBs
1	BRS	L1	5139	torsion\$6 near2 (tool device apparatus)	USPAT; US-PGPUB; EPO; JPO; DERWENT
2	BRS	L2	1941	1 and (sensor detector transducer measur\$5 gauge cell)	USPAT; US-PGPUB; EPO; JPO; DERWENT
3	BRS	L3	1228	2 and (opening bore hole aperture)	USPAT; US-PGPUB; EPO; JPO; DERWENT
4	BRS	L4	755	3 and (handle hold\$5 )	USPAT; US-PGPUB; EPO; JPO; DERWENT
5	BRS	L5	200	4 and (wrench socket)	USPAT; US-PGPUB; EPO; JPO; DERWENT
6	BRS	L6	168	5 and (housing cover\$5 casing)	USPAT; US-PGPUB; EPO; JPO; DERWENT
7	BRS	L7	131	6 and (drive )	USPAT; US-PGPUB; EPO; JPO; DERWENT
8	BRS	L8	72	7 and (body)	USPAT; US-PGPUB; EPO; JPO; DERWENT
9	BRS	L9	41	8 and (sensor detector transducer gauge cell)	USPAT; US-PGPUB; EPO; JPO; DERWENT
10	BRS	L10	0	73/862.210.ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT
11	BRS	L11	52864	(wrench socket).clm.	USPAT; US-PGPUB; EPO; JPO; DERWENT
12	BRS	L12	3217	11 and (sensor detector transducer gauge cell).clm.	USPAT; US-PGPUB; EPO; JPO; DERWENT
13	BRS	L13	885	12 and (handle hold\$5 ).clm.	USPAT; US-PGPUB; EPO; JPO; DERWENT
14	BRS	L14	982	torsion\$6 near2 (tool device apparatus).clm.	USPAT; US-PGPUB; EPO; JPO; DERWENT
15	BRS	L15	156	14 and (sensor detector transducer gauge cell).clm.	USPAT; US-PGPUB; EPO; JPO; DERWENT
16	BRS	L16	42	15 and (opening bore hole aperture).clm.	USPAT; US-PGPUB; EPO; JPO; DERWENT
17	BRS	L17	71167	(wrench socket).ti.	USPAT; US-PGPUB; EPO; JPO; DERWENT
18	BRS	L18	168	17 and (sensor detector transducer gauge cell).clm.	USPAT; US-PGPUB; EPO; JPO; DERWENT
19	BRS	L19	74	18 and (opening bore hole aperture).clm.	USPAT; US-PGPUB; EPO; JPO; DERWENT
20	BRS	L20	27	19 and (flex\$6 deform\$6 bend\$5 )	USPAT; US-PGPUB; EPO; JPO; DERWENT

	Time Stamp	Comments	Error Definition	Errors
1	2004/06/16 11:07			0
2	2004/06/16 11:01			0
3	2004/06/16 11:08			0
4	2004/06/16 11:07			0
5	2004/06/16 10:51			0
6	2004/06/16 10:52			0
7	2004/06/16 10:52			0
8	2004/06/16 11:06			0
9	2004/06/16 11:07			0
10	2004/06/16 11:06			0
11	2004/06/16 11:08			0
12	2004/06/16 11:07			0
13	2004/06/16 11:07			0
14	2004/06/16 11:07			0
15	2004/06/16 11:09			0
16	2004/06/16 11:09			0
17	2004/06/16 11:24			0
18	2004/06/16 11:11			0
19	2004/06/16 11:11			0
20	2004/06/16 11:23			0

	Type	L #	Hits	Search Text	DBs
21	BRS	L21	132	17 and (sensor detector transducer gauge).clm.	USPAT; US-PGPUB; EPO; JPO; DERWENT
22	BRS	L22	46	21 and (opening bore hole aperture).clm.	USPAT; US-PGPUB; EPO; JPO; DERWENT
23	BRS	L23	13	22 and (flex\$6 deform\$6 bend\$5 )	USPAT; US-PGPUB; EPO; JPO; DERWENT
24	BRS	L24	211	73/862.21.ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT
25	BRS	L26	57	24 and (flex\$6 deform\$6 bend\$5 )	USPAT; US-PGPUB; EPO; JPO; DERWENT
26	BRS	L27	40	26 and (opening bore hole aperture)	USPAT; US-PGPUB; EPO; JPO; DERWENT
27	BRS	L28	25	27 and (sensor detector transducer gauge)	USPAT; US-PGPUB; EPO; JPO; DERWENT
28	BRS	L29	22	28 and (wrench socket)	USPAT; US-PGPUB; EPO; JPO; DERWENT

	Time Stamp	Comments	Error Definition	Errors
21	2004/06/16 11:24			0
22	2004/06/16 11:24			0
23	2004/06/16 11:23			0
24	2004/06/16 11:23			0
25	2004/06/16 11:24			0
26	2004/06/16 11:24			0
27	2004/06/16 11:24			0
28	2004/06/16 11:24			0